

JBQI

"JBQI": EQUALISED JUNCTION BOX WITH 4/6 INPUTS, IN IP65 STAINLESS STEEL



Stainless steel junction box with IP65 protection from water and dust, and fitted with electronic board for junction and equalisation of 4 or 6 load cells. Terminal board with screw for easing the connection of the load cells and the signal adjustment trimmer, for an accurate and reliable equalisation.

Working in cooperation with:

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ
Tel. 0040-264566473 Fax. 0040-364-815440
office@cantare.com.ro

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Stainless steel case.
- Protection degree: IP65.
- Maximum input voltage: 24Vdc.
- Maximum input current: 700mA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Protection diodes against surcharges or electrostatic discharges.
- 4 cell inputs on screw connector or on soldering squares (for JB4QI model).
- 6 cell inputs on screw connector or on soldering squares (for JB6QI model).
- Dimensions: 155x158x45mm (lxwxh) for JB4QI
- Dimensions: 190x132x50mm (lxwxh) for JB6QI



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ

Tel. 0040-264566473 Fax. 0040-364-815440

office@cantare.com.ro

SALES AND TECHNICAL ASSISTANCE SERVICE