



Plug in for power supply

PROFESSIONAL LINE

The coaxial model for your LCD / LED-electronic and semi-conductor workstation

Features

- The KERN OZC-5 models are very robust and easy to use trinocular stereo microscopes, with a zoom range operated from both sides and coaxial illumination for above-average images with excellent contrast and depth of field.
- The base is solid and therefore extremely stable.
- Their ideal applications are at monitoring, control and measuring workstations in the semi-conductor, LCD and LED industries, where coaxial illumination is required.
- The parallel optical system allows work without tiring the eyes. In addition, only very minor refocussing at the zoom enlargement is necessary.
- Furthermore, it provides precise resolution, an extra large field of view and is absolutely true-to-colour.
- These models offer the best possible ease of use thanks to their extra large working distance providing a large working surface.
- The multitude of eyepieces and additional accessory parts facilitates use in all common and professional stereo microscopy applications.
- One of the central features of this variable and simultaneously robust series of microscopes is the stable and precisely adjustable mechanism. This is underlined by the functional and ergonomic design.

Technical data

- Optical system: Parallel
- Brightness adjustable
- Magnification ratio: 3,6:1
- Tube: 45° inclined
- Interpupillary distance: 52 - 76 mm
- Diopter adjustment (both-sided)
- Packing dimensions WxDxH 370x330x385 mm
- Net weight approx. 7,1 kg

Please find detailed information in the following charts.

STANDARD



OPTION































Model	Standard configuration					
	Tube	Eyepiece	Field of view mm	Objective Zoom	Stand	Illumination
KERN						
OZC 583	Trinocular	HSWF 10x Ø 23 mm	Ø 12,78 - 3,5	1,8x - 6,5x	Arm curved	2W LED (coaxial incident)

Eyepiece	Specifications - Objectives	
	Magnification	Standard 1,0x
HWF 10x	Total magnification	18x - 65x
	Field of view mm	Ø 12,78 - 3,5
SWF 15x	Total magnification	27x - 97,5x
	Field of view mm	Ø 9,5 - 2,6
SWF 20x	Total magnification	36x - 130x
	Field of view mm	Ø 7,78 - 2,2
SWF 30x	Total magnification	54x - 195x
	Field of view mm	Ø 5 - 1,4
Working distance		92 mm

Model outfit		Model KERN	Order number	
		OZC 583		
Eyepieces	HWF 10x / Ø 23 mm	●●	OZB-A5503	
	SWF 15x / Ø 17 mm	○○	OZB-A5504	
	SWF 20x / Ø 14 mm	○○	OZB-A5505	
	SWF 30x / Ø 9 mm	○○	OZB-A5506	
	HWF 10x / Ø 23 mm (reticule 0,1 mm)	○	OZB-A5512	
	SWF 15x / Ø 17 mm (reticule 0,05 mm)	○	OZB-A5513	
	SWF 20x / Ø 14 mm (reticule 0,05 mm)	○	OZB-A5514	
C-Mount	0,3x	○	OZB-A5701	
	0,5x	○	OZB-A5702	
	1,0x	○	OZB-A5703	
	1,0x (with micrometer)	○	OZB-A5704	
	for SLR cameras (Nikon)	○	OZB-A5706	
	for SLR cameras (Olympus)	○	OZB-A5707	
	for SLR cameras (Canon)	○	OZB-A5708	
Stands	Arm curved, without illumination	●		
Mechanical stage	Stage size: WxD 188x160 mm, Travel: 76x65 mm, for incident and transmitting illumination	○	OZB-A5781	
	Stage size: WxD 180x175 mm, Travel: 100x86 mm, for incident illumination only	○	OZB-A5782	
External illumination	Please find the information about external illumination units in the catalogue from page 68 and on our website www.kern-sohn.com			

● = Standard configuration

○ = Option

 360°	360° rotatable microscope head	 FL-HB0	Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	 AUTO ATC	Automatic temperature compensation For measurements between 10 °C and 30 °C
 MONO	Monocular Microscope For the inspection with one eye	 FL-LED	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	 IP	Protection against dust and water splashes IPxx The type of protection is shown by the pictogram.
 BINO	Binocular Microscope For the inspection with both eyes	 PH	Phase contrast unit For a higher contrast	 BATT	Battery operation Ready for battery operation. The battery type is specified for each device.
 TRINO	Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	 POLAR	Polarising unit To polarise the light	 ACCU	Rechargeable battery pack Rechargeable set.
 ABBE	Abbe Condenser With high numerical aperture for the concentration and the focusing of light	 INFINITY	Infinity system Infinity corrected optical system	 230 V	Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
 HAL	Halogen illumination For pictures bright and rich in contrast	 ZOOM	Zoom magnification For stereomicroscopes	 230 V	Power supply Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
 LED	LED illumination Cold, energy saving and especially long-life illumination	 PARALLEL	Parallel optical system For stereomicroscopes, enables fatigue-proof working	 DAYS	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.
 IL	Incident illumination For non-transparent objects	 SCALE	Integrated scale In the eyepiece	 3 YEARS WARRANTY	Warranty The warranty period is shown in the pictogram.
 TL	Transmitting illumination For transparent objects	 USB 2.0	Integrated USB 2.0 digital camera For direct transmitting of the picture to a PC		
 FL	Fluorescence illumination For stereomicroscopes	 USB 3.0	Integrated USB 3.0 digital camera For direct transmitting of the picture to a PC		

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	N.A.	Numerical Aperture	W.D.	Working Distance
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR Kamera	Single-Lens Reflex camera	WF	Wide Field (Field number up to Ø 22 mm for 10x eyepiece)
LWD	Long Working Distance	SWF	Super Wide Field (Field number at least Ø 23 mm for 10x eyepiece)		

Your KERN specialist dealer: